



EXTREME HEAVY DUTY

BONDS IN EXTREME TEMPERATURES (22°–120°F)

LN-907/LNP-907

Interior/Exterior

A super premium construction adhesive offering outstanding adhesion, durability & performance in extreme conditions

PRODUCT DESCRIPTION

LIQUID NAILS® Extreme Heavy Duty Construction Adhesive, LN-907, offers outstanding adhesion, durability and performance in extreme conditions, bonding in temperatures from 22°F to 120°F. All weather, all season performance helps get the job done right in any condition. Also features a durable plastic tube for outdoor storage all year round. Certified by UL Environment to meet the GREENGUARD GOLD Standard as a low emitting material.

PRODUCT ADVANTAGES

- Bonds in temperatures from 22°F to 120°F for all season performance
- 200% stronger than fasteners alone
- Durable plastic tube for outdoor storage
- VOC compliant
- Exceeds ASTM C-557

RECOMMENDED FOR

Use on a wide range of construction materials, including:

- Plywood
- Waferboard
- Cementboard
- Particleboard
- Treated lumber
- Drywall
- Brick veneers (interior only)
- Imitation stone (interior only)
- Tileboard
- Foamboard
- Ceiling tiles
- 1/8" MDF paneling

Subflooring: Extreme Heavy Duty Adhesive meets the requirements of the APA AFG-01 specification for subfloor installation.

NOT RECOMMENDED FOR

- Plastics
- Vinyl
- Ceramics
- Mirrors
- Granite
- Marble
- Installing tileboard directly to studding, and wood or laminate flooring



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use.

Liquid Nails is a registered trademark of the PPG Group of Companies. UL GREENGUARD is a certification mark of UL LLC. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. © 2022 PPG Industries, Inc. All Rights Reserved. LN_618156 05/22



HEAVY DUTY

STRONG PERMANENT BOND WILL OUTLAST PROJECT

LN-901/LNP-901

Interior/Exterior

A premium, versatile solvent-based adhesive that creates a super strong waterproof & weatherproof bond

PRODUCT DESCRIPTION

LIQUID NAILS® Heavy Duty Construction Adhesive, LN-901/LNP-901, bridges gaps, provides ten minutes working time and produces a durable, flexible, and impact-resistant bond on heavy materials. This formula contains added antioxidants for excellent all-weather performance.

PRODUCT ADVANTAGES

- Strong bond will outlast project
- Waterproof & weatherproof
- Bonds a wide range of construction materials
- Interior & exterior
- Strong, durable & flexible
- Exceptional holding power
- 10 minute working time
- Bridges gaps
- Exceeds ASTM C-557

RECOMMENDED FOR

Bonding common building materials (concrete, lumber, etc.) to:

- Plywood & waferboard
- Treated lumber
- Drywall
- Brick veneers
- Tileboard
- Exterior foamboard (when applied below 90°F)

NOT RECOMMENDED FOR

- Flooring applications
- Ceramics
- Mirrors
- Granite
- Marble (real or cultured)
- Plastic
- Vinyl
- Ceiling tile
- Subfloors/underlayment or 1/8" medium density fiberboard paneling



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use.

Liquid Nails is a registered trademark of the PPG Group of Companies. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. © 2022 PPG Industries, Inc. All Rights Reserved. LN_618156 05/22



PROJECTS

STRONG, DURABLE BOND

LN-704/LNP-704

Interior

A latex-based, VOC-compliant water-resistant construction adhesive that remains flexible, bridges gaps and offers up to 30 minutes working time

PRODUCT DESCRIPTION

LIQUID NAILS® Projects Construction Adhesive, LN-704/LNP-704, offers water clean-up when wet, develops strength rapidly, and has excellent water resistance and long-term holding power when set. Projects Construction Adhesive is certified by UL Environment to meet the GREENGUARD GOLD Standard as a low emitting material.

PRODUCT ADVANTAGES

- Safe for indoor use
- High strength bond
- Easy water clean up
- Bridges gaps up to 3/8"
- No harmful fumes
- Up to 30 minutes open time
- Non staining
- Will not attack foam insulation
- VOC compliant
- Exceeds ASTM C-557

RECOMMENDED FOR

Interior installations and all common building materials, including:

- Paneling
- Corkboard
- Molding
- Foamback tub surrounds
- Drywall
- Furring strips
- Plywood/hardboard
- Masonry/concrete
- Foamboard
- Ceramic tile repairs
- Styrofoam brand insulation
- Foamular rigid foam insulation
- Medium density fiberboard

NOT RECOMMENDED FOR

- Exterior use or for application of ceiling tile
- Finished floors
- Mirrors
- Plastic & vinyl
- Marble & granite
- Foamboard to foamboard
- Basement applications



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use.

Liquid Nails is a registered trademark of the PPG Group of Companies. UL, the UL logos and the UL mark are trademarks of UL LLC. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. © 2022 PPG Industries, Inc. All Rights Reserved. LN_618156 06/22